


CH320

Small Outline Surface Mount Optocoupler Transistor Output Device



Isocom Ltd supplies high reliability devices for applications requiring an operating temperature range of -55°C to +125°C (e.g. military applications).

Devices supplied are approved to BS9400, and have completed rigorous testing. Various high reliability test options are offered.

As a manufacturer of high reliability optocouplers, the Isocom Ltd manufacturing plant in the North East of England has site approval to BS9000 (registration number 1294/M) and CECC20000 (registration number M/1084/CECC/UK) issued by the British Standards Institution.

Together with CECC, BS9000 is a preferred standard for use in European military projects. Consequently, Isocom Ltd's approved devices are listed in the CECC "MUAHAG" preferred products list.

The BS9000 approval is also recognised as meeting the equivalent criteria to those required by BS5750/IS09000/EN29000.

The Company's customers can be assured of our commitment to stringent quality, reliability and inspection standards, as demonstrated by our existing approvals. Other customer specific options can also be offered.

Features	Applications	Circuit Diagram
Small outline package	High density hybrid Sub assembly	
High Radiance LED	Military high rel. systems	
Silicon phototransistor	Switch mode power supplies	
Suitable for hybrid sub assembly mounting	Medical instruments	
Electrical contact by means of wire bonding	System test equipment	
Low input current	Signal transmission between circuit of different potential and impedance	

Description

The CH320 is a single channel device in a small outline package suitable for mounting in hybrid sub-assemblies. Electrical contact is made by wire bonding to the gold thick film contacts on the perimeter of the device.

The device incorporates a high radiance LED and silicon phototransistor. The isolator operational parameters are guaranteed from -55°C to $+125^{\circ}\text{C}$.

Absolute Maximum Ratings

Storage temperature	-65°C to $+150^{\circ}\text{C}$
Operating temperature	-55°C to $+125^{\circ}\text{C}$
Input-to-output isolation voltage	$\pm 500\text{V DC}$

Input Diode

Forward DC current	15mA
Reverse DC voltage	5V
Peak forward current (t = 10 μs duration)	1.5mA
Power Dissipation	25mW

Output Transistor

Collector-emitter voltage BV_{CEO}	30V
Emitter-collector voltage BV_{ECO}	7V
Collector current	20mA
Collector current (t = 1ms)	100mA
Power Dissipation (derate linearly above 100°C at $1.4\text{mW}/^{\circ}\text{C}$)	100mW

Electrical Characteristics ($T_A = -55$ to 125°C U.O.S) *All typical values at $T_A = 25^{\circ}\text{C}$

parameter	symbol	Test Conditions	min	*typ	max	Units
Forward voltage	V_F	$I_F=10\text{mA}$	0.5	1.25	1.5	V
		$I_F=10\text{mA}$ $T_A=125^{\circ}\text{C}$				
		$I_F=10\text{mA}$ $T_A=-55^{\circ}\text{C}$				
Reverse Current	I_R	$V_R=3.0\text{V}$	-	10.5	100	nA
Collector-emitter breakdown voltage	BV_{CEO}	$I_C=1\text{mA}$	30	68.90	-	V
Emitter-collector breakdown voltage	BV_{ECO}	$I_E=10\mu\text{A}$				
Collector-emitter leakage current	I_{CEO}	$V_{\text{CE}}=10\text{V}$, $I_F=0$	<1.0	4.75	100	nA
Collector-emitter leakage current	I_{CEO}	$V_{\text{CE}}=10\text{V}$, $I_F=0$, $T_A=125^{\circ}\text{C}$				
DC current transfer ratio	C.T.R	$I_F=1\text{mA}$, $V_{\text{CE}}=5\text{V}$	12.5	356.11	-	%
DC current transfer ratio	C.T.R	$I_F=1\text{mA}$, $V_{\text{CE}}=5\text{V}$, $T_A=125^{\circ}\text{C}$				
DC current transfer ratio	C.T.R	$I_F=1\text{mA}$, $V_{\text{CE}}=5\text{V}$, $T_A=-55^{\circ}\text{C}$				
Collector-emitter saturation voltage	$V_{\text{CE}}^{(\text{SAT})}$	$I_F=2.0\text{mA}$, $I_C=2.0\text{mA}$	-	139.33	250	mV
Input to output resistance	R_{VO}	$V_{\text{IO}}=500\text{V}$				
Isolation voltage	V_{VO}					
Turn-on time	t_{on}	$R_L=5\text{V}$, $I_F=1\text{mA}$				
Turn-off time	t_{off}	$V_{\text{CC}}=5\text{V}$, $I_F=1\text{mA}$				

Isocom Ltd reserves the right to change the details on this specification without notice. Please consult Isocom Ltd prior to use. Isocom Ltd cannot accept liability for any errors or omissions.

For sales enquiries, or further information, please contact our sales office at:

Isocom Ltd, Hutton Close, Crowther Industrial Estate, District 3, Washington, NE38 0AH

Tel: +44 0191 4166 546 Fax: +44 0191 4155 055 Email Isocom@isocomptocouplers.com

Or go to the Isocom Website @: [Http://www.isocom.uk.com](http://www.isocom.uk.com)