

TLP620-2 TRANSISTOR AC INPUT OPTOCOUPLEDERS

ISOCOM[®] LTD

| PACKAGES | CIRCUIT |
|----------|---------|
| | |

DESCRIPTION

The TLP620-2 is a dual channel device. Each channel consisting of a bi-directional input opto-isolator consists of two Gallium Arsenide infrared emitting diodes connected in inverse parallel coupled to a silicon NPN phototransistor in a 8 pin package.

Isocom Ltd supplies a multitude of plastic optocouplers for all applications varying from standard transistor optos through to Darlington and Schmitt Trigger devices. It's massive family of optos vary in speed allowing maximum opportunity to engineers worldwide.

All devices are performance guaranteed between -20°C and +80°C and have completed rigorous testing. The Company's customers can be assured of our commitment to stringent quality, reliability and inspection standards, as demonstrated by our existing approvals. Other customer specific options can also be offered.

FEATURES

- 5000V Isolation
- AC or Polarity Insensitive Inputs
- Compact Dual-in-line Package
- Built-in Reverse polarity Input Protection
- Current Transfer Ratio (Min 20% at $I_F = \pm 1\text{mA}$, $V_{CE} = 5\text{V}$)
- UL Recognised, file No E64380

Isocom Ltd reserves the right to change the details on this specification without notice. Please consult Isocom Ltd prior to use. Isocom Ltd cannot accept liability for any errors or omissions.

For sales enquiries, or further information, please contact our sales office at:

Isocom Ltd, Hutton Close, Crowther Industrial Estate, District 3, Washington, NE38 0AH

Tel: +44 0191 4166 546 Fax: +44 0191 4155 055 Email Isocom@isocomptocouplers.com

Or go to the Isocom Website @: [Http://www.isocom.uk.com](http://www.isocom.uk.com)

ABSOLUTE MAXIMUM RATINGS

| | |
|-----------------------------------|-------------------------------|
| Storage Temperature | -55°C to +125°C |
| Operating Temperature | -30°C to +100°C |
| Lead Soldering Temperature | 260°C 1.6mm from case for 10S |
| Input-to-Output Isolation Voltage | 5000VDC |

Input Diode

| | | |
|----------------------|-------|--|
| Forward DC Current | ±50mA | |
| Peak forward Current | ±1.0A | |
| Power Dissipation | 70mW | |

Output Transistor

| | | |
|----------------------------|-------|------------|
| Collector-Emitter Voltage | 35V | BV_{CEO} |
| Emitter-Collector voltage | 6V | BV_{ECO} |
| Collector-Current | 50mA | I_C |
| CollectorPower Dissipation | 150mW | P_C |

Package

| | | |
|-------------------------|-------|-----------|
| Total Power Dissipation | 200mW | P_{tot} |
|-------------------------|-------|-----------|

ELECTRICAL CHARACTERISTICS

$T_A = 25^\circ\text{C}$ U.O.S. (each channel where appropriate).

Input Diode Electrical Characteristics

| Parameter | Symbol | Test Conditions | Device | Min | Typ | Max | Units |
|----------------------|----------|----------------------------|--------|-----|-----|-----|-------|
| Forward Voltage | V_F | $I_F = \pm 20\text{mA}$ | | | 1.2 | 1.4 | V |
| Peak Forward Voltage | V_{FM} | $I_{FM} = \pm 0.5\text{A}$ | | | | 3.0 | V |
| Terminal Capacitance | C_t | $V = 0, f = 1\text{KHz}$ | | | 50 | 250 | pF |

Output Detector Electrical Characteristics

| | | | | | | | |
|--------------------------------|-----------|--------------------------------|--|--|--|-----------|---|
| Collector-emitter Dark Current | I_{CEO} | $V_{CE} = 20\text{V}, I_F = 0$ | | | | 10^{-7} | A |
|--------------------------------|-----------|--------------------------------|--|--|--|-----------|---|

Coupled Electrical Characteristics

| | | | | | | | |
|--------------------------------------|---------------|---|--|--------------------|-----------|-----|---------------|
| Current Transfer ratio | CTR | $I_F = \pm 1\text{mA}, V_{CE} = 5\text{V}$ | | 20 | | 300 | % |
| Collector-Emitter saturation voltage | $V_{CE(sat)}$ | $I_F = \pm 20\text{mA}, I_C = 1\text{mA}$ | | | 0.1 | 0.2 | V |
| Isolation Resistance | R_{ISO} | DC= 500V, 40 to 60% RH | | 5×10^{10} | 10^{11} | | Ω |
| Floating Capacitance | C_f | $V = 0, f = 1\text{MHz}$ | | | 0.6 | 1.0 | pF |
| Cut-off Frequency | f_c | $V_{CE} = 5\text{V}, I_C = 2\text{mA}, R_L = 100\Omega$ | | 15 | 80 | | KHz |
| Response time (Rise) | t_r | $V_{CC} = 2\text{V}, I_C = 2\text{mA}, R_L = 100\Omega$ | | | 4 | 18 | μS |
| Response time (Fall) | t_f | | | | 3 | 18 | μS |
| Isolation Voltage | V_{ISO} | | | 5000 | | | V |

Isocom Ltd reserves the right to change the details on this specification without notice. Please consult Isocom Ltd prior to use.

Isocom Ltd cannot accept liability for any errors or omissions.

For sales enquiries, or further information, please contact our sales office at:

Isocom Ltd, Hutton Close, Crowther Industrial Estate, District 3, Washington, NE38 0AH

Tel: +44 0191 4166 546 Fax: +44 0191 4155 055 Email Isocom@isocomptocouplers.com

Or go to the Isocom Website @: [Http://www.isocom.uk.com](http://www.isocom.uk.com)